


EVO 360



Model	PU	VP	Art. Nr.	EAN
EVO 360	1		71017801	9002719041658



Characteristics

- For use in horizontal or vertical operation
- Particularly easy and safe operation even for less experienced users
- Protection class IP66
- Very high accuracy
- Plumbing point for marking out right angles
- Automatic height monitoring, stops the laser in the event of strong vibrations

Applications

- Horizontal leveling
- Vertical leveling

Manufacturer

SOLA-Messwerkzeuge GmbH & Co KG
Unteres Tobel 25
6840 Götztis, Austria
T +43 5523 533800
www.sola.at, sola@sola.at

Technical details

Item description	Horizontal/vertical rotation laser
Dimensions	179 x 143 x 211 mm
Leveling	automatic
Measuring tolerance	±0.10 mm/m
Self-leveling range	±5°
Application range without handheld receiver (radius)	20 m*
Application range with handheld receiver (radius)	300 m*
Operating temperature	-10°C to +50 °C
Rotation speed	600 rpm
Tripod adapter	5/8"
Protection class	IP66
Power supply	2 x 3.6 V (18650) Li-ion battery (2 x 3450 mAh)
Operating time (at 20 °C)	40 hrs
Laser class	2M, DIN EN 60825-1:2014+A1:2017
Output power	< 1.0 mW
Wavelength	635 - 650 nm

Included accessory

- REC RRD1 receiver with bracket
- Rechargeable battery cell 18650
- Charger
- Power plug
- EVO 360 case



SOLA-Messwerkzeuge GmbH & Co KG
Unteres Tobel 25
6840 Götztis, Austria
T +43 5523 53380-0
sola@sola.at, www.sola.at

SOLA-Messwerkzeuge GmbH & Co. KG
Heuriedweg 69
88131 Lindau, Germany
T +49 8382 28585
sola@sola.at, www.sola.de

SOLA Suisse AG
Grenzstrasse 24
9430 St. Margrethen, Switzerland
T +41 71 740 1616
info@solasuisse.ch
www.solasuisse.ch